

Material Safety Data Sheet

Carburetor Choke & Throttle Body Cleaner

August 25, 2009

SECTION - 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Berryman Products, Inc.
3800 E. Randol Mill Rd
Arlington, TX 76011-5434
800-433-1704

Part No.: 0101C, 0105C, 0117C, 0120C, 2401C, 2405C, 2420C, 2421C.
www.berrymanproducts.com
EMERGENCY TELEPHONE NUMBER
INFOTRAC (800) 535-5053

SECTION - 2 COMPOSITION INFORMATION

COMPONENT	CAS#	% BY WEIGHT
Acetone	67-64-1	80 - 92%
Toluene	108-88-3	10 - 15%
2-Butoxyethanol	111-76-2	2 - 5%
Methanol	67-56-1	1 - 2%
Isopropanol	67-63-0	1 - 2%
Methyl Ethyl Ketone	78-93-3	1 - 2%
Xylene	1330-20-7	1 - 2%
Amyl Acetate	628-63-7	0.1 - 1%

SECTION - 3 HAZARDS INFORMATION

EMERGENCY OVERVIEW

DANGER! Extremely Flammable Liquid and Vapor. Vapor May Cause Flash Fire. Harmful If Swallowed or Inhaled. Causes Irritation to Skin, Eyes and Respiratory Tract. Affects Central Nervous System. Do not allow material to contaminant water sources. Sara Title III Reporting.

ACUTE —Effects Of Single Overexposure

EYES Product contact with eyes can cause irritation. Vapor effects may cause eye irritation experienced as discomfort, redness or pain.

SKIN Product contact with skin can cause irritation, dryness and cracking may occur.

INHALATION Product is irritating to respiratory tract, can cause dizziness, drowsiness, depression, narcosis and headaches.

INGESTION Harmful If Swallowed. Swallowing this material may cause stomach or intestinal upset with pain, nausea, and/or diarrhea.

CHRONIC —Prolonged or Repeated Overexposure

EYES Product contact with eyes can cause irritation and corneal damage. Prolonged contact can cause conjunctivitis, blurred or dimmed vision with optic neuritis, eye pain, atrophy, concentric visual fields, and photophobia, followed by transient or permanent, complete or bilateral blindness.

SKIN Product can be absorbed through skin and can affect Target Organs. Effects include central nervous system depression, narcosis, optic neuritis, and acidosis. Skin absorption may cause similar effects as from breathing or swallowing.

INHALATION Product is irritating to respiratory tract and can affect Target Organs. Can cause central nervous system depression and peripheral nervous system effects. Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage sometimes referred to as "Solvent or Painter's Syndrome".

INGESTION Harmful or Fatal If Swallowed. Can affect Target Organs. Blindness, liver, kidney and brain damage can occur.

ASPIRATION Vomiting can cause serious inflammation and accumulation of fluids in the lungs. (Pneumonitis and pulmonary edema)

HAZARD Aspiration into the lungs can produce severe lung damage and is a medical emergency.

TARGET ORGANS Kidneys, Liver, Eyes, Hearing, Lungs, Brain, Skin, Central and Peripheral Nervous System, Gastrointestinal and Cardiovascular Systems.

CARCINOGENIC —Product may contain trace amounts of following.

CHEMICAL	CAS#	NTP	ACGIH	IARC	PERCENT
Ethylbenzene	100-41-4	Yes	(A3) Proven for animal	(2B) Possible for human	< 0.3%

MUTAGENIC AND TERATOGENIC EFFECTS —May cause fetal and reproductive abnormalities.

CHEMICAL	CAS#	PERCENT
Toluene	108-88-3	10 - 15%
Methanol	67-56-1	1 - 2%
Xylene	1330-20-7	1 - 2%

HAZARD RATINGS	Health	Flammability	Reactivity	Personal Protection
HMIS	2	3	0	G = Safety glasses, gloves, vapor respirator

SECTION - 4		FIRST AID MEASURES					
EYE CONTACT	Immediately flush eyes with cold water for at least 15 minutes while lifting upper and lower eyelids. Be sure to remove any contact lenses. Obtain immediate medical attention.						
SKIN CONTACT	Immediately flush skin with plenty of water for at least 15 minutes while removing any contaminated clothing or shoes. Cover the irritated skin with an emollient. Obtain medical attention if irritation persists. Wash any contaminated clothing and/or shoes before reuse.						
INHALATION	Remove person to fresh air, if they have problem breathing or any signs of overexposure, obtain immediate medical attention.						
INGESTION	DO NOT INDUCE VOMITING. If person is fully conscious give one to two glasses of water to dilute and obtain immediate medical attention.						
ASPIRATION HAZARD	If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician or hospital emergency room immediately.						
SECTION - 5		FIRE FIGHTING MEASURES					
COMPONENT (Acetone)	FLASH POINT -16°C (3°F)	METHOD TAG Closed Cup		NFPA Class Class IB	FLAMMABILITY CLASSIFICATION Flammable Liquid		
FLAMMABLE LIMITS	LOWER 2.6%	UPPER 12.8%		AUTO-IGNITION TEMPERATURE 225°C (437°F)			
EXPLOSION HAZARDS	Mechanical Impact Not Expected			Static Discharge Expected			
Reactive with	Acids and oxidizers such as chlorine and other halogens, chromates, perchlorates, peroxides and oxygen.						
Extinguishing Media	Use DRY chemicals, CO ₂ , alcohol foam. Water spray to cool or protect exposed materials.						
Fire Fighting Procedures	May explode if ignited in an enclosed area. Flashback along vapor trail may occur.						
Protective Equipment	Use MSHA/NIOSH approved self-contained breathing apparatus and full protective gear. (Full Bunker Gear)						
Hazardous Decomposition	Burning or thermal decomposition can produce carbon monoxide and/or carbon dioxide and other toxic fumes.						
HAZARD RATINGS	Health	Flammability	Reactivity	Specific Hazard			
NFPA	2	3	0				
SECTION - 6		ACCIDENTAL RELEASE MEASURES					
SPILL OR LEAK	DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. Warn personal to move away and eliminate ignition sources and ventilate area. Wear the appropriate safety equipment. Contain spill or stop the flow and absorb with an inert material and place in an appropriate waste disposal unit and dispose of in accordance with all State and Federal Guidelines and Regulations.						
SECTION - 7		HANDLING AND STORAGE					
HANDLING	EXTREMELY FLAMMABLE LIQUID AND VAPOR, Avoid flame, sparks static discharge and all electric devices. Avoid inhalation of vapors or contact with eyes or skin. Do not allow material to contaminant water sources. Open container slowly to relieve pressure. Bond and ground all equipment when transferring from one vessel to another. Can accumulate static discharge by flow or agitation. The use of explosion-proof equipment is recommended and may be required. Wash thoroughly after handling and do not wear any contaminated clothing or shoes.						
STORAGE	Keep container tightly closed when not in use and store in a cool, well-ventilated area away from direct sunlight or any ignition sources. Use proper signage. Store only in approved containers. Keep away from incompatible materials listed in Section 10. Storage should meet OSHA and NFPA standards for Class-1B flammable liquids.						
SECTION - 8		EXPOSURE CONTROLS / PERSONAL PROTECTION					
EXPOSURE LIMITS COMPONENT	ACGIH TWA8	ACGIH TWA8	OSHA PEL TWA8	OSHA PEL TWA8	ACGIH STEL	ACGIH STEL	Significant Exposure
Acetone	500 ppm A4		1000 ppm		750 ppm		
Toluene	50 ppm		200 ppm				
2-Butoxyethanol	25 ppm	121 mg/m ³	25 ppm	120 mg/m ³			Skin
Methanol	200 ppm	260 mg/m ³	250 ppm	310 mg/m ³	250 ppm	310 mg/m ³	Skin
Isopropyl Alcohol	400 ppm	980 mg/m ³	400 ppm	980 mg/m ³	500 ppm		
Methyl Ethyl Ketone	200 ppm		200 ppm		300 ppm		
Xylene Isomers	100 ppm	434 mg/m ³	100 ppm	435 mg/m ³	150 ppm	651 mg/m ³	
Amyl Acetate	50 ppm		100 ppm	525 mg/m ³	100 ppm		

SECTION - 8		EXPOSURE CONTROLS / PERSONAL PROTECTION CONTINUED			
PERSONAL PROTECTION					
EYES	Safety goggles or face shield.	HANDS	Butyl or neoprene gloves.		
BODY	Not normally required.	FEET	Not normally required.		
RESPIRATORY	Wear MSHA/NIOSH approved respirator or equivalent.	OTHER	Eye bath and safety shower.		
VENTILATION	Ventilate to keep vapors of this material below the lowest ppm listed above. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus.				
SECTION - 9		PHYSICAL AND CHEMICAL PROPERTIES			
PHYSICAL STATE	Liquid	pH	Not applicable		
APPEARANCE	Clear	SPECIFIC GRAVITY	0.80		
ODOR	Solvent	DENSITY	7.3 lb/gal		
SOLUBILITY	< 85%	FREEZE POINT	Not determined		
VOLATILES	100%	VAPOR PRESSURE	Not determined		
V.O.C.	20%	VAPOR DENSITY	Not determined		
SECTION - 10		STABILITY AND REACTIVITY			
CONDITIONS TO AVOID	Heat sources				
INCOMPATIBLE MATERIALS	Extremely reactive and incompatible with concentrated oxygen, acids, bases and oxidizing agents. These include liquid bleach, sodium or calcium hypochlorite, halogens, permanganates, sulfuric acid, nitric acid, sodium or potassium hydroxide, isocyanides, hydrogen peroxide and acetaldehyde.				
THERMAL DECOMPOSITION	Burning or thermal decomposition can produce carbon monoxide and/or carbon dioxide and other toxic fumes.				
HAZARDOUS POLYMERIZATION	Will not occur.				
SECTION - 11		TOXICOLOGICAL INFORMATION			
COMPONENT		FORM	SUBJECT	RESULT VALUE	EXPOSURE TIME
Acetone	LD50	Oral	Rabbit	5340 mg/kg	
Toluene	LD50	Oral	Rat	2.6 to 7.5 g/kg	
	LC50	Inhaled	Rat	8000 ppm	4 Hr
	LD50	Oral	Rat	2.6 to 7.5 g/kg	
2-Butoxyethanol	LC50	Inhaled	Rat	8000 ppm	4 Hr
	LD50	Skin	Rabbit	220 mg/kg	
	LD50	Skin	Guinea Pig	> 2000 mg/kg	
Methanol	LC50	Inhaled	Rat	700 ppm	7 Hr
	LD50	Oral	Rat	5628 mg/kg	
	LD50	Skin	Rabbit	15800 mg/kg	
Isopropyl Alcohol	LC50	Inhaled	Rat	64000 ppm	4 Hr
	LD50	Oral	Mouse	3800 gm/kg	
	LD50	Oral	Rabbit	6410 mg/kg	
	LD50	Oral	Rat	5045 mg/kg	
Methyl Ethyl Ketone	LD50	Skin	Rabbit	12800 mg/kg	
	LD50	Oral	Rat	2737 mg/kg	
	LC50	Skin	Rabbit	23,500 mg/m ³	8 Hr
	LD50	Oral	Rabbit	6480 mg/m ³	
Xylene Isomers	LD50	Oral	Rat	4300 mg/kg	
	LC50	Inhaled	Rat	5000 ppm	4 Hr
	LD50	Oral	Rat	4300 mg/kg	
Amyl Acetate	LC50	Inhaled	Rat	5000 ppm	4 Hr
	LD50	Oral	Rat	6,500 mg/kg	
	LD50	Skin	Rabbit	8327 mg/kg	

SECTION - 12		ECOLOGICAL INFORMATION					
COMPONENT		SUBJECT	RESULT VALUE	EXPOSURE TIME			
Acetone	LC50	Mosquito Fish	13000 mg/L	48 Hr			
Toluene	LC50	Fish	10 to 100 mg/L	96 Hr			
2-Butoxyethanol	LC50	Daphnia magna	835 mg/L				
	EC50	Water flea	2500 mg/L				
	LC50	Flathead Minnow	1900 mg/L				
Methanol	LC50	Lepomis macrochirus	435 mg/L				
	LC50	Goldfish	250 ppm	11 Hr			
	LC50	Rainbow trout	8000 mg/L	48 Hr			
	LC50	Flathead Minnow	29.4 g/L	96 Hr			
Isopropyl Alcohol	LC50	Goldfish	5000 mg/L	24 Hr			
	LC50	Flathead Minnow	11830 mg/L	1 Hr			
	LC50	Fish	> 100 gm/L	96 Hr			
Methyl Ethyl Ketone	LC50	Oncorhynchus mykiss	8.2 mg/L	96 Hr			
Xylene	LC50	Lepomis macrochirus	12 mg/L	96 Hr			
	LC50	Pimephales promelas	13.3 mg/L	96 Hr			
	LC50	Fish	10 to 100 mg/L	96 Hr			
Amyl Acetate	LC50	Fish	10 to 100 mg/L	96 Hr			
SECTION - 13		DISPOSAL CONSIDERATIONS					
DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. Dispose of any waste in accordance with all State and Federal Guidelines and Regulations.							
ENVIRONMENTAL FATE This material, as supplied, when discarded or disposed of, is a hazardous waste according to Federal Regulations (40 CFR 261) due to its ignitability and due to the composition containing some or all of its components. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the material is a hazardous waste.							
The transportation, storage, treatment and disposal of RCRA waster material must be conducted in compliance with 40 CFR 262, 263, 264 and 270. Disposal can only occur in property permitted facilities, Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate.							
SECTION - 14		TRANSPORT INFORMATION					
D.O.T. CLASSIFICATION							
UN NUMBER	PROPER SHIPPING NAME	n.o.s.		HAZARD CLASS			
UN1993	FLAMMABLE LIQUID	(Acetone, Toluene, Methanol)		3			
PACKING GROUP	LABEL CODES	REPORTABLE QUANTITY	RESPONSE CODE	MARINE POLLUTANT			
PGII	Flammable liquid	1000 LBS	127 (Acetone) 130 (Toluene)	No			
SECTION - 15		REGULATORY INFORMATION					
TSCA		Sec 8(b)	Sec 8(d)	Sec 4(a)	Sec 12(b)		
Chemical Name	CAS No.	Inventory	Health & Safety	Chemical Test Rules	Export Notification		
Acetone	67-64-1	Yes		Yes	Yes		
Toluene	108-88-3	Yes	Yes				
2-Butoxyethanol	111-76-2	Yes					
Methanol	67-56-1	Yes	Yes		Yes		
Isopropyl Alcohol	67-63-0	Yes	Yes	Yes	Yes		
Methyl Ethyl Ketone	78-93-3	Yes					
Xylene, all isomers	1330-20-7	Yes	Yes	Yes			
Amyl Acetate	628-63-7	Yes					
HCS CLASSIFICATION							
Flammable Liquid having a flash point lower than 23°C (73°F) (Acetone, Toluene, Methanol)							
REPORTABLE QUANTITIES		Extremely Hazardous		Reportable Quantity	Emission Reporting		
Chemical Name	CAS No.	EPCRA TPQ Sec. 302	EPCRA RQ Sec. 304	CERCLA RQ Sec. 103	TRI Sec. 313	RCRA Code	RMP TQ Sec112r
Acetone	67-64-1			5,000		U002	
Toluene	108-88-3			1,000	Yes	U220	
Methanol	67-56-1			5,000	Yes	U154	
Isopropyl Alcohol	67-63-0				Yes		
Methyl Ethyl Ketone	78-93-3			5,000	Yes	U159	
Xylene	1330-20-7			100	Yes	U239	
Amyl Acetate	628-63-7			5,000			

SECTION - 15		REGULATORY INFORMATION CONTINUED												
SARA		Sec 311						Sec 311 & 312 Hazards						
Chemical Name	CAS No.	Hazardous Chemical						Acute	Chronic	Flammable	Pressure	Reactive		
Acetone	67-64-1	Yes						Yes		Yes				
Toluene	108-88-3	Yes						Yes	Yes	Yes				
2-Butoxyethanol	111-76-2	Yes						Yes	Yes	Yes				
Methanol	67-56-1	Yes						Yes	Yes	Yes				
Isopropyl Alcohol	67-63-0	Yes						Yes	Yes	Yes				
Methyl Ethyl Ketone	78-93-3	Yes						Yes		Yes				
Amyl Acetate	628-63-7	Yes						Yes						
RIGHT TO KNOW		State												
Chemical Name	CAS No.	CA	CT	FL	IL	LA	NJ	NY	PA	MI	MN	MA	RI	WI
Acetone	67-64-1						Yes		Yes					
Toluene	108-88-3	Yes		Yes			Yes		Yes		Yes	Yes		Yes
Isopropyl Alcohol	67-63-0	Yes		Yes			Yes		Yes		Yes	Yes		Yes
Methanol	67-56-1	Yes												
Methyl Ethyl Ketone	78-93-3	Yes		Yes			Yes		Yes		Yes	Yes		
Xylene	1330-20-7	Yes		Yes	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes
Amyl Acetate	628-63-7	Yes									Yes			
CALIFORNIA		WARNING! This product contains chemicals known to the state of California to cause:												
Proposition 65	CAS No.	Birth Defects			Reproductive Harm			Carcinogen			Developmental			
Ethylbenzene	100-41-4	Yes			Yes			Yes			Yes			
Toluene	108-88-3	Yes			Yes						Yes			
Methanol	67-56-1	Yes			Yes									
Clean Air & Water Acts		Clean Air Acts						Clean Water Acts						
Chemical Name	CAS No.	HAP		Ozone Class 1		Ozone Class 2		HS	PP	TP				
Ethylbenzene	100-41-4	Yes						Yes	Yes	Yes				
Toluene	108-88-3	Yes						Yes						
Methyl Ethyl Ketone	78-93-3	Yes												
Xylene (mixed isomers)	1330-20-7	Yes						Yes						
Methanol	67-56-1	Yes						Yes						
INTERNATIONAL REGULATIONS - The components of this product are listed on the chemical inventories of the following countries														
Chemical Name	CAS No.	Australia	Canada	Europe (EINECS)			Japan	Korea	UK					
Ethylbenzene	100-41-4	Yes	Yes	Yes			Yes	Yes	Yes					
Isopropyl Alcohol	67-63-0	Yes	Yes	Yes			Yes	Yes	Yes					
Methyl Ethyl Ketone	78-93-3	Yes	Yes	Yes			Yes	Yes	Yes					
Methanol	67-56-1	Yes	Yes	Yes			Yes	Yes	Yes					
DSCL (EEC)	Code	Definition (Risk-Phrases / Safety-Phrases)												
	R11	Highly Flammable												
	R36/38	Irritating to eyes and skin.												
	R37/38	Irritation to respiratory system and skin.												
	R65	Harmful: may cause lung damage if swallowed.												
	S16	Keep away from sources of ignition. No Smoking.												
	S36/37	Wear suitable protective clothing and gloves												
	S61	Avoid release to the environment. Refer to special instructions/safety data sheet												
	S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label												
WHMIS Classification														
Chemical name	DSL	Class	Definition											
Acetone	Yes	B2	Flammable liquid with a flash point lower than 37.8°C (100°F)											
Toluene	Yes	B2												
Methyl Ethyl Ketone	Yes	B2												
Xylene (mixed isomers)	Yes	B2												
Methanol	Yes	D2B	Materials Causing Other Toxic Effects - Toxic Material											
Ethylbenzene	Yes	D2B												

SECTION - 16		OTHER INFORMATION		
SOURCE INFORMATION		CHEMICAL	CAS NO.	REVISION DATE
Conchemco, LTD		Acetone	67-64-1	11/12/2006
CITGO Petroleum Corporation		Toluene	108-88-3	6/18/2007
Conchemco, LTD		Methyl Ethyl Ketone	78-93-3	11/12/2006
Conchemco LTD		2-Propanol	67-63-0	11/12/2006
CITGO		Xylene (mixed isomers)	1330-20-7	6/19/2007
EQUISTAR		Methanol	67-56-1	10/16/2001
Dow Chemical		Primary Amyl Acetate	628-63-7	7/16/2008
MSDS Legend				
ACGIH	= American Conference of Governmental Industrial Hygienists	NFPA	= National Fire Protection Association	
CAS	= Chemical Abstracts Service Registry	n.o.s.	= Not Otherwise Specified	
CEILING	= Ceiling Limit (15 minutes)	NTP	= National Toxicology Program	
CERCLA	= The Comprehensive Environmental Response, Compensation, and Liability Act	OSHA	= Occupational Safety and Health Administration	
EPA	= Environmental Protection Agency	PEL	= Permissible Exposure Limit (OSHA)	
HAP	= Hazard Air Pollutant	PP	= Priority Pollutant	
HMIS	= Hazardous Materials Identification System	SARA	= Superfund Amendments and Reauthorization Act	
HS	= Hazardous Substance	STEL	= Short Term Exposure Limit (15 minutes)	
IARC	= International Agency for Research on Cancer	TLV	= Threshold Limit Value (ACGIH)	
LEL	= Lower Explosive Limit	TP	= Toxic Pollutant	
NE	= Not Established	TWA	= Time Weighted Average (8 hours)	
		UEL	= Upper Explosive Limit	
		WHMIS	= Worker Hazardous Materials Information System (Canada)	
DISCLAIMER				
The information herein has been compiled from sources believed to be reliable and up-to-date, and is accurate to the best of our knowledge. However, Berryman Products, Inc and/or nCites, LLC cannot give any guarantees regarding information from other sources or completeness and expressly does not make warranties, nor assumes any liability for its use. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries, losses, or damages to persons or property arising from the use of this product or information.				